



invisiron®  
sentry S-6000



# sentry S-6000

## Super Charged Defence System

Invisiron® Sentry S-6000 is built for large networks and data centres. Supports up to 2 x 10GB ports and copper as well as fibre-optic connections.

## Key Features

### Automatic Threat Mitigation

Invisiron® offers a pro-active Cyber Defence platform with auto threat mitigation in real-time 24/7. No user intervention is needed.

### DDoS Protection<sup>1</sup>

We are able to mitigate both volumetric and protocol-based DDoS attacks.

### Advanced Threat Protection

Our device protects your organisation against advanced persistent threats and many other attacks and malware.

### Data Exfiltration

Our DNS threat analytics ruleset is able to detect and automatically block data exfiltration attempts via DNS.

### Cyber Threat Intelligence (Invisiron-CTI™)

Invisiron-CTI™ comes from over 30 globally validated sources, which are updated and pushed down to every Invisiron® device every hour, automatically.

### Threat Commander Remote Monitoring Utility

Every malicious packet that is mitigated by Invisiron® can be reviewed in our Remote Monitoring System and allows our Managed Detection and Response (MDR) teams to perform forensics on compromised assets.

### Bi-Directional Deep Packet Inspection (DPI)

Based on our 7 Threat Intelligence, entire packet contents are inspected and filtered bi-directionally via our state-of-the-art architecture.

### Invisible Stealth Mode

Invisiron® devices do not require a MAC or IP address to operate. Hackers will not be able to detect the presence of an Invisiron device in a network.

### Ultra-Fast In-Line Packet Processing Speed

Packets are processed at near line speed without degradation of your Internet bandwidth.

### No Changes to Existing Network Infrastructure

A plug-and-play complete Cyber Defence solution, without having the need to make any changes to existing IT infrastructure networks.

### Geo IP Blocking

Invisiron® devices are able to block network connections based on geographical locations and countries.

### High Availability

Invisiron® devices supports High Availability.

<sup>1</sup> Only Applicable to S-6000DDoS

# Designed for Large Enterprises & Data Centres



## Technical Specifications

Processor	Intel Xeon
Memory	16 GB of DDR4 memory
Storage	HPE Dynamic Smart Array configured in disk mirroring mode
Disk Drives	2x 1TB low form factor SATA disk drives
Packet Processing	2x 10GB Ethernet ports. High performance Intel NIC with SFP Optical as well as copper SFP modules supported
Management	1GB Ethernet (RJ45) for Management
Power and Cooling	Dual redundant 900W switching power supplies, 100-240 Volt AC High efficient cooling for warm environments
Form Factor	2U - 43.47 cm (W) x 63.43 cm (D) x 8.76 cm (H)
Embedded OS	Linux
Cyber Threat Intelligence	Cloud-based Invisiron-CTI™
DPI Rules	Up to 10,000 rules
Reputation Detection	Up to 2,000,000 domain names and URLs
IP Address Filtering	Up to 250,000 IP addresses, both IPV4 and IPV6
DGA Detection	Supported on DNS queries and replies
Configuration	Graphical User Interface over encrypted link
Alerts and Notifications	By Graphical User Interface, E-Mails
Evidence Collection	Packets captured in PCAP data format. Event logging in JSON format
System Upgrades	Software updates provided from the cloud



## PT. Giwang Kanaka

Alamat :

Jl. Batanghari No. 23 A, Cideng - Gambir

Jakarta Pusat 10150

+6221385 7272 (Hunting)

info@giwangkanaka.co.id

Cyber   
Defence  
Fortified™